

Limited Site Assessment Report Former UST-25, Building 25 at Post Lane

Marine Corps Base Camp Lejeune Jacksonville, Onslow County, North Carolina

Task Order Number: WE31

July 2011

Prepared for

Department of the Navy
Naval Facilities Engineering Command
Mid-Atlantic

Under the

NAVFAC CLEAN 1000 Program Contract Number N62470-08-D-1000

Prepared by



3201 Beechleaf Court, Suite 300 Raleigh, North Carolina 27604 NC Engineering License F-0699

Contents

Acro	onyms and Abbreviations	v
Purj	pose of Investigation	vii
1	Site Information 1.1 Site Identification 1.2 Release Information 1.3 Certification	1-1 1-1
2	Site History and Characterization 2.1 Site Description 2.2 Environmental History of Building 25.	2-1
3	Risk Characterization 3.1 Groundwater/Surface Water/Vapor Impacts 3.1.1 High Risk 3.1.2 Intermediate Risk 3.2 Land Use 3.2.1 Property Containing Source Area of Release 3.2.2 Property Surrounding Source Area of Release	3-1 3-1 3-2 3-3
4	Receptor Information	4-1 4-1 4-1 4-1 4-2
5	Geology and Hydrogeology	5-1
6	Sampling Results 6.1 Soil Sampling 6.1.1 Soil Analytical Results 6.2 Groundwater Sampling 6.2.1 Groundwater Analytical Results 6.3 Free Product Investigation/Recovery 6.4 Investigation-derived Waste Management	
7	Conclusions and Recommendations	7-1
0	B. Carrette	0.1

Figures

- 2-1 Base Location Map
- 2-2 Topographic Site Location Map
- 2-3 Site Map
- 3-1 Land Use and Receptor Survey Map

Tables

- 2-1 UST System and Site History
- 4-1 Deep Aquifers of the Coastal Plain
- 4-2 Property Owners and Occupants
- 6-1 Soil Analytical Results
- 6-2 Monitoring Well Construction Details
- 6-3 Water Quality Measurements
- 6-4 Groundwater Analytical Results

Appendixes

- A Soil Boring Log and Well Completion Diagram
- B Groundwater Sampling Data Sheet
- C Soil and Groundwater Analytical Laboratory Reports and Chain-of-Custody Forms

IV ES051611232936WDC

Acronyms and Abbreviations

AHEC AH Environmental Consultants

amsl above mean sea level
AST above ground storage tank

bgs below ground surface

CERCLA Comprehensive Environmental Response, Compensation, and Liability Act

CVOC chlorinated volatile organic compound

DOT Department of Transportation

EPH extractable petroleum hydrocarbons

ESCTP Environmental Security Technology Certification Program

FID flame ionization detection

Fm Formation ft foot/feet ft/day feet per day

GCL gross contamination level

ID inner diameter

IDW investigation-derived waste IRP Installation Restoration Program

ISCO in-situ chemical oxidation

lbs pounds

LSA Limited Site Assessment

LUC land use control

μg/kg micrograms per kilogram μg/L micrograms per liter

MADEP Massachusetts Department of Environmental Protection

MCB CamLej Marine Corps Base Camp Lejeune

mg/kg milligrams per kilogram

MSCC maximum soil contamination concentration

NAVFAC Naval Facilities Engineering Command Mid-Atlantic NCDEH North Carolina Department of Environmental Health

NCDENR North Carolina Department of Environment and Natural Resources

NCGWQS North Carolina Groundwater Quality Standard

ORP oxidation-reduction potential

OU Operable Unit

PCE tetrachloroethene ppm parts per million

RI Remedial Investigation

ES051611232936WDC V

SEAR surfactant enhanced aquifer remediation

SVOC semi-volatile organic compound SWAP Source Water Assessment Program

TCE trichloroethene

TPH total petroleum hydrocarbons

USEPA United States Environmental Protection Agency

UST underground storage tank

VOC volatile organic compound

VPH volatile petroleum hydrocarbons

WHPP Wellhead Protection Program

wt. by weight

ZVI zero valent iron

VI ES051611232936WDC

Purpose of Investigation

The purpose of this Limited Site Assessment (LSA) is to provide the North Carolina Department of Environment and Natural Resources (NCDENR) Division of Waste Management, Underground Storage Tank (UST) Section with the necessary information to classify the level of environmental risk associated with a petroleum release at former UST-25. This LSA was conducted by CH2M HILL for the Naval Facilities Engineering Command Mid-Atlantic (NAVFAC) in accordance with the December 2008, NCDENR *Guidelines for Assessment and Corrective Action for UST Releases* (UST *Guidelines*), amended with updated regulatory standards in January 2010 (NCDENR 2008, 2010a, 2010b), and the *Work Plan for Phase I Limited Site Assessments and Administrative Closure at UST/AST Sites* (CH2M HILL, 2010).

ES051611232936WDC VII

Site Information

1.1 Site Identification

Date of Report: July 2011
Facility ID: 0-002740
UST Incident # 32405

UST Number WI-7278 (also listed as WI-474)

Site Name: Former UST-25, Former Building 25 on Post Lane

Location: MCB CamLej, Onslow County, North Carolina

Nearest City/Town: Jacksonville

UST Owner Commanding General – MCB Camp Lejeune

I&E/EMD/EQD

PSC 2004

MCB Camp Lejeune, NC 28542-0004

910-451-5068

UST Operator Same As Above Property Owner Same As Above

Property Occupant Parking lot for administrative offices

Located between Post Lane and Virginia Dare Drive

Consultant/Contractor: CH2M HILL, Inc.

3201 Beechleaf Court, Suite 300

Raleigh, NC 27604

Analytical Laboratory Katahdin Analytical

600 Technology Way Scarborough, ME 04074

1.2 Release Information

Date Release Discovered: 1995

Estimated Quantity of Release: Unknown

Potential Source of Release: Former UST

Size and Content of UST: Five 750-gallon tanks for storing Varsol™

ES051611232936WDC 1-1

Latitude and Longitude:

N 34° 40′ 16.723″

W 77° 20′ 55.011″

1.3 Certification

I, <u>Daniel Hockett</u> a certified Professional Engineer/ icensed Geologist (circle one) for CH2M HILL, do certify that the information contained in this report is correct and accurate to the best of my knowledge.

- Harry

C Literate No. 2

1-2 ES051611232936WDC

Site History and Characterization

2.1 Site Description

Marine Corps Base Camp Lejeune (MCB CamLej) encompasses approximately 236 square miles of land in Onslow County, NC, adjacent to the southern boundary of the City of Jacksonville (**Figure 2-1**). Jacksonville is the largest city near MCB CamLej and contains approximately half of the county's total population. Since 1990, much of the MCB CamLej complex has been part of Jacksonville. The remaining areas adjacent to the Base are generally rural. The Base is bordered by the Atlantic Ocean to the south, U.S. Route 17 to the west, State Route 24 to the north, the town of Hubert, North Carolina, to the east, and is bisected by the New River, which flows into the Atlantic Ocean in a southeasterly direction.

The former underground storage tank (UST) system was located at the former Base Dry Cleaning Facility (former Building 25) on Post Lane, approximately 500 feet (ft) east of the intersection of Post Lane and McHugh Boulevard, on the Mainside portion of MCB CamLej. **Figure 2-2** illustrates the location of UST-25. The site is currently an asphalt parking lot. UST-25 is located within the bounds of an Installation Restoration Program (IRP) site, managed under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) program, known as Operable Unit (OU) 15, Site 88.

2.2 Environmental History of Building 25

The former Base Dry Cleaning Facility (former Building 25) operated from the 1940s until 2004. Five USTs were reportedly installed in the 1940s to be used in conjunction with dry cleaning operations at Building 25. VarsolTM, a petroleum distillate, was initially used; however, because of flammability concerns, Varsol's use was discontinued in the 1970s and was replaced with tetrachloroethene (PCE) (Baker, 1998). During this time, PCE was stored in one 150-gallon aboveground storage tank (AST) adjacent to the north wall of former Building 25, in the same vicinity as the USTs (**Figure 2-3**). Dry cleaning operations ceased in January 2004 and Building 25 was demolished in August 2004.

In 1995, OHM was contracted to remove all of the USTs associated with former Building 25. During the excavation activities, conducted between September 1995 and March 1996, OHM removed the five 750-gallon USTs adjacent to former Building 25. The UST closure activities included the disposal of approximately 140 tons of soil affected by releases of chlorinated volatile organic compounds (CVOCs) and 3,180 gallons of liquids from within the USTs (OHM, 1996). The dimensions of the five 750-gallon USTs were approximately 6- ft long by 4.5-ft in diameter, and were located approximately 1.5-ft below ground surface (bgs). The UST system information is summarized in **Table 2-1**.

Confirmation soil samples collected from the base of the excavation and each sidewall indicated the presence of CVOCs, including PCE, prompting additional excavation and soil sampling along the east wall. Additional excavation could not be conducted along the south wall because of the presence of the building (OHM, 1996). Total petroleum hydrocarbons

ES051611232936WDC 2-1

(TPH) were detected in the five confirmation samples at concentrations ranging from 41 to 820 milligrams per kilogram (mg/kg), which exceeded North Carolina action levels. Four temporary groundwater monitoring wells were installed in the vicinity of the UST basin and former Building 25. Laboratory analysis of soil samples collected during well installation did not detect TPH. However, TPH was detected in two of the four groundwater samples collected from the temporary wells at concentrations that exceeded the North Carolina action level. CVOCs were also detected in the groundwater samples at concentrations that exceeded the North Carolina Groundwater Quality Standards (NCGWQS) (OHM, 1996).

On May 2, 2001, UST-25 was transferred from the North Carolina Department of Environment and Natural Resources (NCDENR) UST Program to Site 88 because of the discovery of CVOC contamination in soil and groundwater in the vicinity of the former USTs. The original UST closure assessment did not utilize the current NCDENR UST Program risk-based methodologies, and a Limited Site Assessment (LSA) was not conducted for UST-25 prior to transfer to the IRP.

In 1999, a surfactant enhanced aquifer remediation (SEAR) demonstration was conducted within a 20-ft by 30-ft area at the site. The custom surfactant used in the demonstration consisted of 4% by weight (wt.) surfactant, 12% wt. isopropanol, and 0.16 to 0.19% wt. calcium chloride mixed with potable water. During the demonstration, approximately 29,700 gallons of surfactant was injected into the subsurface in the vicinity of the former UST basin, equivalent to 9,718 pounds (lbs) of surfactant, 38,637 lbs of isopropanol, and 427 lbs of calcium chloride. Over the course of the SEAR demonstration, the surfactant was continuously injected, a total of 286,000 gallons of fluid (a mixture of surfactant, dense non-aqueous phase liquid, and groundwater) were extracted, and a total of 76 gallons of PCE were removed (Duke, 2000).

Following several phases of investigation and the pilot testing of remedial technologies at Site 88, including the former UST-25 tank basin, an area of 10,000 square feet was treated using soil mixing. The treatment area included the former UST-25 tank basin and extended to a depth of approximately 20 ft bgs. The soil mixing activities utilized a 10-ft diameter auger to homogenize the soils while injecting a slurry of zero valent iron (ZVI) and bentonite clay (Figure 2-3) (CH2M HILL, 2008a). The ZVI created a strongly reducing environment to promote destruction of the CVOCs, while the bentonite clay facilitated uniform distribution of the iron during the mixing process and reduced the hydraulic conductivity within the treatment zone. USTs were not encountered during the soil mixing activities.

Between 2002 and 2007, a Remedial Investigation (RI) was completed at Site 88. The RI reported the presence of benzene in a groundwater sample collected from monitoring well IR88-MW30 at a concentration of 10 micrograms per liter (μ g/L), exceeding the NCGWQS (**Figure 2-3**). However, the RI concluded that this and other detections of petroleum hydrocarbons did not pose an unacceptable human health risk.

In June 2009, a geophysical investigation was conducted in the vicinity of former Building 25 (**Figure 2-3**) to search for the presence of anomalies indicative of a UST. An as-built drawing of former Building 25 indicated nine USTs were present at the site; however, upon excavation of the tanks, only five USTs were present. The five identified USTs were removed. The geophysical investigation was conducted to determine if any additional USTs

2-2 ES051611232936WDC

were present at the site. The geophysical investigation did not detect geophysical anomalies that suggested the presence of USTs (CH2M HILL, 2009).

In 2010, an in-situ chemical oxidation (ISCO) demonstration using polymer-enhanced permanganate was conducted adjacent to former UST-25 as part of the Environmental Security Technology Certification Program (ESCTP). The study included permanganate-only injections and polymer-enhanced permanganate injections for remediation of volatile organic compounds (VOCs) adjacent to the tank basin.

ES051611232936WDC 2-3

Risk Characterization

This section presents a summary of the information necessary to assign a risk classification for the site. The questionnaire format was provided in the UST *Guidelines – Appendix B* (NCDENR, 2008).

3.1 Groundwater/Surface Water/Vapor Impacts

3.1.1 High Risk

1. Has the release contaminated any water supply well including any well used for non-drinking purposes?

NO.

2. Is a water supply well used for drinking water located within 1,000 ft of the source area of the release?

NO: There are no water supply wells within 1,000 ft of the source area, as shown on **Figure 3-1**. The nearest active water supply well, PSW-HP652, is located 10,000 ft to the east.

3. Is a water supply well not used for drinking water (e.g., irrigation, washing cars, industrial cooling water, filling swimming pools) located within 250 ft of the source area of the release?

NO: No non-potable water supply wells are located within 250 ft of the source area.

4. Does groundwater within 500 ft of the source area of the release have the potential for future use (there is no other source of water supply other than the groundwater)?

NO: A municipal water supply is available to the area. There are no plans for water supply wells to be installed and utilized within 500 ft of the source area.

5. Do vapors from the release pose a threat of explosion because of accumulation of the vapors in a confined space or pose other threats to public health, public safety, or the environment?

NO: The location of the former USTs is an open parking lot. The maximum flame ionization detection (FID) reading from the headspace of a resealable plastic bag containing subsurface soil samples was 31.2 parts per million (ppm) and the air monitoring during soil sampling activities indicated that the explosive gas concentrations were below the lower explosive limit.

ES051611232936WDC 3-1

6. Are there any other factors that would cause the release to pose an imminent danger to public health, public safety, or the environment?

NO: Petroleum contaminated soil was excavated during UST removal activities in 1995 and 1996, and the site is currently capped by asphalt parking areas. CVOC-contaminated soil and groundwater are currently being addressed as part of the ongoing studies at Site 88.

3.1.2 Intermediate Risk

1. Is a surface water body located within 500 ft of the source area of the release?

NO: The nearest surface water body is an unnamed tributary to Beaverdam Creek, located approximately 1,050 ft northeast.

2. Is the source area of the release located within an approved or planned wellhead protection area as defined in 42 USC 300h-7(e)?

NO: The nearest wellhead protection area is located approximately 6 miles northeast of the site, according to the NCDENR Public Water Supply Well Section's Wellhead Protection Program (WHPP) Source Water Assessment Program (SWAP) website. The source area is not located within a MCB CamLej designated wellhead protection area, according to the most recent Wellhead Protection Plan- 2002 Update (AHEC, 2002).

3. Is the release located in the Coastal Plain physiographic region as designated on a map entitled "Geology of North Carolina" published by the Department in 1985?

YES: MCB CamLej is located within the Coastal Plain physiographic province.

If YES, is the source area of the release located in an area in which there is recharge to an unconfined or semi-confined deeper aquifer that is being used or may be used as a source of drinking water?

NO: The potential source area is located above the semi-confined Castle Hayne aquifer. While there is potential for recharge to the surficial and Castle Hayne aquifers, untreated groundwater is not used on MCB CamLej as drinking water. Groundwater obtained from the Castle Hayne aquifer is the raw water source for the MCB CamLej potable water treatment facilities. There is not a raw water supply well located within 10,000 ft of the potential source area.

4. Do the levels of groundwater contamination for any contaminant exceed the gross contamination levels (GCLs) established by the Department?

YES: Indeno(1,2,3-cd)pyrene was detected at an estimated concentration of 0.11 μ g/L that exceeded the NCGWQS and GCL, which are both 0.05 μ g/L.

3-2 ES051611232936WDC

3.2 Land Use

3.2.1 Property Containing Source Area of Release

1. Does the property contain one or more primary or secondary residences (permanent or temporary)?

NO: The potential source area does not contain primary or secondary residences. The nearest military barracks are located approximately 200 ft east of the former source area.

2. Does the property contain a school, daycare center, hospital, playground, park, recreation area, church, nursing home, or other place of public assembly?

NO: There are no places of public assembly located on the property.

3. Does the property contain a commercial (e.g., retail, warehouse, office/business space, etc.) or industrial (e.g., manufacturing, utilities, industrial research and development, chemical/petroleum bulk storage, etc.) enterprise, an inactive commercial or industrial enterprise, or is the land undeveloped?

NO: The property is an asphalt parking lot surrounded by landscaped areas. Military administrative offices are located in the immediate surrounding area but not in the former UST basin or former Building 25.

4. Do children visit the property?

NO: Children were not observed during the site assessment activities and, under normal circumstances, are not expected to visit the property.

5. Is access to the property reliably restricted consistent with its use (e.g., by fences, security personnel, or both)?

YES: The property/site is located within the MCB CamLej military installation. There is a minimum of one layer of security designed to prohibit trespassers or other unauthorized access to facilities on the base.

6. Do pavements, buildings, or other structures cap the contaminated soil?

YES: Petroleum contaminated soil was excavated during the UST removal and the tank basin was capped with asphalt. Additionally, CVOC-contaminated soil in the vicinity of the former UST basin was remediated through soil mixing and portions of the soil mixing zone were capped with asphalt.

If yes, what mechanisms are in place or can be put into place to ensure that the contaminated soil will remain capped in the foreseeable future?

Although future use cannot be reliably predicted, the site is likely to remain capped by asphalt for the foreseeable future. In addition, it is anticipated that remedial actions for Site 88 will include land use controls (LUCs) limiting soil and groundwater use within the former UST basin.

ES051611232936WDC 3-3

7. What is the zoning status of the property?

MCB CamLej is not subject to local zoning requirements; however, the site is consistent with Industrial/Commercial properties.

8. Is the use of the property likely to change in the next 20 years?

The area has historically been used for military administrative purposes and the use of the property is not likely to change in the next 20 years. Furthermore, the soil mixing resulted in unstable soils, restricting development of the site to its current use as a parking lot.

3.2.2 Property Surrounding Source Area of Release

1. What is the distance from the source area of the release to the nearest primary or secondary residence (permanent or temporary)?

The nearest military barracks are located approximately 200 ft east of the former source area.

2. What is the distance from the source area of the release to the nearest school, daycare center, hospital, playground, park, recreation area, church, nursing home, or other place of public assembly?

The nearest place of public assembly is the Jewish Chapel located approximately 450 ft northwest of the former source area.

3. What is the zoning status of properties in the surrounding area?

MCB CamLej is not subject to local zoning requirements; however, the surrounding properties are consistent with Industrial/Commercial properties.

4. Briefly characterize the use and activities of the land in the surrounding area.

The surrounding area is primarily used for administrative facilities, with some barracks and training areas also located in the area.

3-4 ES051611232936WDC

Receptor Information

4.1 Water Supply Wells

There are no water supply wells within 1,500 ft of former UST-25 (**Figure 3-1**).

4.2 Public Water Supplies

There are no public water supply sources present within 1,500 ft of former UST-25. Potable water is supplied to the base by the MCB CamLej water supply system. The raw water supply for MCB CamLej and the surrounding areas is provided by water supply wells that pump groundwater from the Castle Hayne aquifer. The nearest active water supply well, PSW-HP652, is located 10,000 ft to the east.

4.3 Surface Water

An unnamed tributary to Beaverdam Creek is located approximately 1,050 ft to the northeast of former UST-25. The creek drains into Beaverdam Creek, which drains into Wallace Creek and, ultimately, the New River.

4.4 Wellhead Protection Area

Based on information provided by the North Carolina Department of Environmental Health (NCDEH) — Public Water Supply Section, as of January 2011, there are no approved wellhead protection areas with 1,500 ft of former UST-25 (NCDEH, 2011). Additionally, MCB CamLej has established wellhead protection areas in the WHPP – 2002 Update (AHEC, 2002). According to the WHPP, the site is not located within a wellhead protection area.

4.5 Deep Aquifers in the Coastal Plain Physiographic Region

Southeastern North Carolina and MCB CamLej are within the Tidewater region of the Atlantic Coastal Plain physiographic province. Within the MCB CamLej area, approximately 1,500 ft of sediment overlies the basement rock. These sediments contain seven aquifers and their associated confining units and include the Surficial, Castle Hayne, Beaufort, Peedee, Black Creek, and Upper and Lower Cape Fear aquifers (Cardinell, et al., 1993).

Data were obtained from boring logs and cross-sections developed as part of the IRP Site 88 investigations. Aquifers in the vicinity of the source area are summarized on **Table 4-1**.

ES051611232936WDC 4-1

TABLE 4-1
Deep Aquifers of the Coastal Plain
Former UST-25 Phase I LSA Report
MCB CamLej, North Carolina

Hydrogeologic Unit	Approximate Depth Interval (ft bgs)
Surficial aquifer	8 to 20
Castle Hayne Confining Unit	20 to 35
Castle Hayne Aquifer	35 to 175
Beaufort Confining Unit	175 to 185
Beaufort Aquifer	185

The nearest area of groundwater discharge downgradient from the site is the New River, located 2,900 ft west of the source area.

4.6 Subsurface Structures

Subsurface utilities, including water and sewer pipes, are located in the vicinity of the source area. There were no basement structures observed in the surrounding area. The threat of explosion due to the accumulation of vapors from an underground contaminant source to a confined space is not likely based on explosive gas measurements obtained during soil sampling.

4.7 Property Owners and Occupants

Table 4-2 lists the property owner and occupant information.

TABLE 4-2 Property Owners and Occupants Former UST-25 Phase I LSA Report MCB CamLej, North Carolina

Tax Parcel Number	Owner/Occupant Name	Address
Unknown – 236 square miles of	Commanding General – MCB	I&E/EMD/EQD
land within MCB CamLej	CamLej, NC	PSC 20004
		MCB Camp Lejeune, NC 28542

4-2 ES051611232936WDC

Geology and Hydrogeology

5.1 Site Geology

Site-specific geological information was obtained during the installation of monitoring well IR88-MW31, constructed within the former UST-25 basin. The soil boring log and well completion diagram for monitoring well IR88-MW31 are included as **Appendix A**.

Shallow soils of the undifferentiated formation near the source area consist of mostly fine silt to approximately 18 ft bgs underlain by a clayey silt layer of the Belgrade Formation. In the vicinity of former UST-25, this clayey silt layer extends to approximately 30 ft bgs. The River Bend and Castle Hayne Formations (Fms) are located below this layer and consist of fine to medium-grained sands with intermittent beds of partially cemented and shelly sand to approximately 180 ft bgs. A laterally continuous clay layer, approximately 10 ft thick, is encountered below the Castle Hayne Fm.

5.2 Site Hydrogeology

Investigations of Site 88 and UST-25 have focused upon the surficial aquifer and underlying Castle Hayne aquifer which occur within the shallow deposits of the undifferentiated formation, and the River Bend and Castle Hayne Formations, respectively. These aquifers are occasionally separated by a discontinuous layer of clayey silt that occurs at a depth of roughly 20 to 25 ft bgs and pinches out to the west of UST-25. The presence of this fine grained layer beneath the former footprint of Building 25 inhibits downward movement of groundwater.

The soil mixing activities introduced ZVI and bentonite clay that significantly reduced the hydraulic conductivity of the soils within the former UST-25 tank basin to approximately 0.013 feet per day (ft/day) (AGVIQ/CH2M HILL, 2006). Laboratory testing of undisturbed soil samples collected from the clayey silt aquitard yielded vertical hydraulic conductivity values of 1.3×10^{-4} ft/day (CH2M HILL, 2008a).

During the November through December 2010 field event, the depth to water in IR88-MW31 was between 17.64 and 17.70 ft above mean sea level (amsl). Groundwater flow within the surficial aquifer is generally toward the southwest. Groundwater flow in the Castle Hayne aquifer is generally to the west, northwest.

ES051611232936WDC 5-1

Sampling Results

The Phase I LSA investigation included collection of a groundwater sample from existing well IR88-MW31 and installation of one soil boring immediately adjacent to monitoring well IR88-MW31, within the former UST-25 tank basin, as shown on **Figure 2-3**. Analytical results from the Phase I LSA activities are discussed as follows.

6.1 Soil Sampling

The soil boring location was selected to evaluate subsurface soil conditions within the former UST basin. On December 13, 2010, one subsurface soil sample (UST25-SB01-4-5-10D) was collected using a stainless steel hand auger from a depth of 4 to 5 ft bgs. This sample interval was selected because it was approximately one foot above the water table (6.42 ft bgs), as measured in monitoring well IR88-MW31.

The soil sample was analyzed by the following laboratory methods:

- VOCs (United States Environmental Protection Agency [USEPA] Method 8260)
- Semi-volatile organic compounds (SVOCs) (USEPA Method 8270)
- Volatile petroleum hydrocarbons (Massachusetts Department of Environmental Protection [MADEP] VPH)
- Extractable petroleum hydrocarbons (MADEP EPH)

A portion of the sample, intended for VOC analysis, was field preserved by field preparation method 5035 to limit volatilization of VOCs. The remaining soil sample was placed into a stainless steel bowl, homogenized, and then transferred into the appropriate bottleware. The soil samples were placed into an ice-filled sample cooler, accompanied by chain-of-custody, and shipped by overnight courier to Katahdin Analytical Services in Scarborough, Maine.

6.1.1 Soil Analytical Results

A summary of analytes detected in the soil sample is presented in **Table 6-1** (modified from NCDENR UST Table B-3). The complete analytical laboratory report is presented in **Appendix C**. To determine the risk classification, the analytical results were compared to the Soil-to-Groundwater Maximum Soil Contamination Concentrations (MSCCs), the Industrial/Commercial MSCCs, and the Residential MSCCs specified in Table 4 of the UST *Guidelines* (NCDENR, 2008, 2010a).

Seventeen VOCs were detected in the soil sample, of which three were detected at concentrations exceeding their respective Soil-to-Groundwater MSCC. The concentrations of benzene (17 J micrograms per kilogram [μ g/kg]), PCE (25,000 J μ g/kg), and trichloroethene (TCE) (29 J μ g/kg) exceeded their respective Soil-to-Groundwater MSCCs. Additionally, the concentration of PCE exceeded the Residential MSCC and the Industrial/Commercial MSCCs. No petroleum-related hydrocarbons were detected at concentrations exceeding their respective Industrial/Commercial MSCCs.

ES051611232936WDC 6-1

Sixteen SVOCs were detected in the soil sample; however, none of the detected concentrations of SVOCs exceeded their respective MSCCs.

One EPH fraction (C9-C18 aliphatics) and one VPH fraction (C9-C22 aromatics) were detected in the soil sample at concentrations of 140,000 and 130,000 μ g/kg, respectively. Only the concentration of C9-C22 aromatics fraction exceeded the Soil-to-Groundwater MSCC (31,000 μ g/kg). None of the detected concentrations of EPH or VPH exceeded their respective Industrial/Commercial or Residential MSCCs.

6.2 Groundwater Sampling

One groundwater sample was collected from monitoring well IR88-MW31 on November 30, 2010 (**Figure 2-3**). This monitoring well is located immediately adjacent to the former tank basin. Well construction information for IR88-MW31 is summarized in **Table 6-2**, and the well completion diagram is included in **Appendix A**.

The monitoring well was purged and sampled using low flow sampling methodology. A submersible bladder pump equipped with new ¼-inch inner diameter (ID) polyethylene tubing was placed at the midpoint of the well screen and operated until water quality parameters including pH, temperature, oxidation-reduction potential (ORP), turbidity, and conductivity stabilized. The water quality parameters were monitored using a calibrated YSI 556 multi-parameter system with a flow-through cell and recorded on groundwater sampling data sheets (**Appendix B**). A summary of groundwater quality parameters are shown on **Table 6-3**.

Following purging, groundwater samples were collected for laboratory analysis of:

- VOCs (USEPA Method 8260),
- SVOCs (USEPA Method 8270)
- MADEP VPH, and
- MADEP EPH

The groundwater samples were placed in laboratory-supplied bottleware, then placed into an ice-filled cooler, were accompanied by chain-of-custody, and shipped via Federal Express to Katahdin Laboratories in Scarborough, Maine.

6.2.1 Groundwater Analytical Results

A summary of analytes detected in the groundwater sample collected from well IR88-MW31 is presented on **Table 6-4**. The complete analytical laboratory report is included as **Appendix C**.

Four VOCs (benzene, ethylbenzene, total xylenes, and toluene) and five SVOCs (2-methylnaphthalene, di-n-butylphthalate, fluorene, indeno(1,2,3-cd)pyrene, and naphthalene), were detected in the groundwater sample collected from IR88-MW31. Benzene was detected at a concentration (120 μ g/L), exceeding the NCGWQS of 1 μ g/L, but below the applicable GCL of 5,000 μ g/L. Indeno(1,2,3-cd)pyrene exceeded the NCGWQS and GCL of 0.05 μ g/L.

6-2 ES051611232936WDC

One EPH (C9-C12 aliphatics) and two VPH fractions (C5-C8 aliphatics and C9-C10 aromatics) were detected in the groundwater sample. The C9-C12 aliphatics concentration, C5-C8 aliphatics, and C9-C22 aromatics exceeded their respective NCGWQS.

6.3 Free Product Investigation/Recovery

Free product was not detected in monitoring well IR88-MW31.

6.4 Investigation-derived Waste Management

Investigation-derived waste (IDW) generated during the LSA field activities was containerized in Department of Transportation (DOT)-approved 55-gallon steel drums and staged at the temporary storage facility located at Mainside on MCB CamLej. A licensed IDW contractor transported the IDW to an approved waste facility for disposal.

ES051611232936WDC 6-3

Conclusions and Recommendations

7.1 Conclusions

Based on the results of this Phase I LSA for the former UST-25 tank basin, the following conclusions are presented:

- There are no water supply wells within 1,500 ft of UST-25.
- Potable water throughout the base is supplied by the MCB CamLej Public Works Department.
- The former UST-25 tank basin is not located in a designated wellhead protection area.
- No surface water bodies are located within 500 ft of the source area.
- The site should be classified as Industrial/Commercial land use.
- Three VOCs (benzene, PCE, and TCE) were detected in soil samples at concentrations exceeding their respective Soil-to-Groundwater MSCC. PCE was the only VOC reported to exceed its respective Industrial/Commercial and Residential MSCC (10,000 μ g/kg) at a concentration of 25,000 J μ g/kg.
- Petroleum-related hydrocarbons were not detected in the subsurface soil sample at concentrations above Industrial/Commercial and Residential MSCCs. Only the C9-C22 aromatics fraction exceeded the Soil-to-Groundwater MSCC (31,000 μg/kg).
- Benzene was detected in groundwater above the NCGWQS, but below the GCL of 5,000 μ g/L. Indeno(1,2,3-cd)pyrene was detected at an estimated concentration (0.11 J μ g/L) that exceeded the NCGQWS and GCL of 0.05 μ g/L.
- C9-C18 aliphatics, C5-C8 aliphatics, and C9-C22 aromatic hydrocarbon fractions detected in groundwater exceeded the NCGWQSs.
- The CVOCs (PCE, TCE and daughter products) are being addressed through the IRP at Site 88 where a pilot study is currently being conducted and the final remedial action is planned to be in-place in 2014.

7.2 Recommendations

Based on the detection of indeno(1,2,3-cd)pyrene above the GCL at an estimated concentration of 0.11 J μ g/L, the site does not qualify for low risk classification. It is recommended that additional groundwater samples be collected for analysis of SVOCs in one year. Upon completion of the additional sample collection, the risk classification of the site can be reevaluated.

ES051611232936WDC 7-1

References

AGVIQ/CH2M HILL. 2006. Site 88 Building 25 Source Removal Non-time Critical Removal Action Report, Operable Unit 15, Marine Corps Base Camp Lejeune, North Carolina. August.

AH Environmental Consultants (AHEC). 2002. Wellhead Protection Plan - 2002 Update, Marine Corps Base Camp Lejeune, North Carolina. August.

Baker Environmental Inc. (Baker). 1998. Focused Remedial Investigation Report, Operable Unit No. 15 (Site 88), Marine Corps Base Camp Lejeune, North Carolina. May.

Cardinell, A.P., S. A. Berg, and O. B. Lloyd, Jr. 1993. *Hydrogeologic Framework of U.S. Marine Corps Base at Camp Lejeune, North Carolina*. Water Resources Investigations U.S. Geological Survey: Report 93-4049.

CH2M HILL. 2008a. Remedial Investigation, Site 88, Operable Unit No. 15, Marine Corps Base Camp Lejeune, Jacksonville, North Carolina. March.

CH2M HILL. 2008b. Master Project Plans, Marine Corps Base Camp Lejeune, Jacksonville, North Carolina.

CH2M HILL. 2009. *Geophysical Investigation Results, Operable Unit 15 (Site 88), Marine Corps Base, Camp Lejeune, North Carolina*. October.

CH2M HILL. 2010. Work Plan for Phase I Limited Site Assessments and Administrative Closure at UST/AST Sites, Marine Corps Base Camp Lejeune, Jacksonville, North Carolina. November.

Duke Engineering and Services. 2000. Surfactant-Enhanced Aquifer Remediation Demonstration at Site 88, Marine Corps Base Camp Lejeune, North Carolina. January.

North Carolina Department of Environment and Natural Resources (NCDENR). 2008. *Guidelines for Assessment and Corrective Action for UST Releases*. Division of Waste Management, Underground Storage Tank Section. December.

NCDENR. 2010a. *Maximum Soil Contaminant Concentration Levels (MSCCs)*. Division of Waste Management, Underground Storage Tank Section. January. http://portal.ncdenr.org/web/wm/ust/guidance.


NCDENR. 2010b. *Gross Contamination Levels for Groundwater Table*. Division of Waste Management, Underground Storage Tank Section. January. http://portal.ncdenr.org/web/wm/ust/guidance.


NCDEH. 2011. Public Water Supply Section. January. http://www.deh.enr.state.nc.us/pws/index.htm

OHM Remediation Services Corp. (OHM). 1996. *Contractor's Closeout Report: Underground Storage Tank Removals at Building 25, MCB Camp Lejeune, Jacksonville, North Carolina*. October.


ES051611232936WDC 8-1

Figures









Tables

TABLE 2-1
UST System and Site History
Former UST-25 Phase I LSA Report
MCB CamLej, North Carolina

UST ID Number	Previous Content	Capacity (gallons)	Construction Details	Tank Dimensions (feet)	Description of Associated Piping and Pumps	Date tank installed	Status of UST	Release associated with the UST?
UST-25-1 through 5	Varsol [™]	750	Steel	6 x 4.5	Piping to building has been removed	1940s	Removed 1995-1996	Yes

TABLE 6-1Soil Analytical Results
Former UST-25 Phase I LSA Report
MCB CamLej, North Carolina

	Soil-to-		Industrial/	
	Groundwater	Residential	Commerical	
Sample ID	MSCC	MSCC	MSCC	UST25-SB01-4-5-10D
Sample Date		111000	MICOC	12/13/10
				12/13/10
Chemical Name				
Volatile Organic Compounds (μg/kg)	202	4 400 000	00 000 000	7.0.1
1,2-Dichlorobenzene	230	1,400,000	36,000,000	7.8 J
1,3,5-Trimethylbenzene	8,300	782,000	20,440,000	770 J
1,4-Dichlorobenzene	99	110,000	1,000,000	2.8 J
2-Butanone	NS	NS 11 000 000	NS	40 J
Acetone	24,000	14,000,000	360,000,000	340 J
Benzene	5.6	18,000	164,000	17 J
cis-1,2-Dichloroethene	350	156,000	4,000,000	2.1 J
Ethylbenzene	4,900	1,560,000	40,000,000	10 J
Isopropylbenzene	1,700	1,564,000	40,880,000 81,760,000	41 J 21 J
m- and p-Xylene	4,600	3,129,000		
n-Butylbenzene	4,300	626,000	16,350,000	88 J
o-Xylene	4,600	3,129,000	81,760,000	40 J
sec-Butylbenzene	3,300	626,000	16,350,000	170 J
tert-Butylbenzene	3,400	626,000	16,350,000	32 J
Tetrachloroethene	7.4	1,100	10,000	<u>25,000</u> <u>J</u>
Toluene	4,300	1,200,000	32,000,000	16 J
Trichloroethene	19	4,600	120,000	29 J
Semivolatile Organic Compounds (μg/kg)	0.500	700.000	00.440.000	400 1
1,2,4-Trimethylbenzene	8,500	782,000	20,440,000	480 J
2-Methylnaphthalene	3,600	63,000	1,635,000	22 J
Acenaphthene	8,200	940,000	24,000,000	12 J
Acenaphthylene	11,000	469,000	12,264,000	1.9 J
Benzo(a)anthracene	350	880	8,000	9.9 J
Benzo(a)pyrene	96	88	780	7 J
Benzo(b)fluoranthene	1,200	880	8,000	12 J
Benzo(g,h,i)perylene	6,400,000	469,000	12,264,000	5.8 J
Benzo(k)fluoranthene	12,000	9,000	78,000	3.9 J
Chrysene	39,000	88,000	780,000	2.9 J
Fluoranthene	290,000	620,000	16,400,000	24
Fluorene	47,000	620,000	16,400,000	13 J
Indeno(1,2,3-cd)pyrene	3,400	880	8,000	5.2 J
Naphthalene	160	313,000	8,176,000	17 J
Phenanthrene	56,000	469,000	12,264,000	34
Pyrene	270,000	469,000	12,264,000	24
VPH/EPH (µg/kg)				
Aliphatics C9-C12				140,000
Aliphatics C9-C12 Aliphatics C9-C18	540,000	1,500,000	40,000,000	75,000 U
·				
Aromatics C9-C10	31,000	469,000	12,264,000	130,000
Aromatics C11-C22				18,000 U

Bold text indicates exceedance of Soil-to-Groundwater MSCC

Underlined text indicates exceedance of Residential MSCC

Bold box indicates exceedance of Industrial/Commercial MSCC

J - Analyte present, value may or may not be accurate or precise

U - The material was analyzed for, but not detected

μg/kg - Micrograms per kilogram

VPH - volatile petroleum hydrocarbons

EPH - extractable petroleum hydrocarbons

NS - Not specified

TABLE 6-2 Monitoring Well Construction Details Fomer UST- 25 Phase I LSA Report MCB Cam Lej, North Carolina

Monitoring Well ID	Date Installed	Date Water Level Measured	Casing Diameter (inches)	Screened Interval (ft bgs)	TOC Elevation (ft amsl)	Well Depth (ft bgs)	Depth to water (ft btoc)	Water Elevation (ft amsl)
IR88-MW31	10/13/2005	12/13/2010	2	3 to 18	24.95	18	7.31	17.64

ft amsl - feet above mean sea level ft bgs - feet below ground surface ft btoc - feet below top of casing

TABLE 6-3
Water Quality Measurements
Former UST-25 Phase I LSA Report
MCB CamLej, North Carolina

Monitoring Well ID	Date Sampled	Depth to Water (ft btoc)	TOC Elevation (ft amsl)	Water Elevation (ft amsl)	pH (SU)	Conductivity (mS/cm)	Dissolved Oxygen (mg/L)	Temperature (°Celsius)	Turbidity (NTU)	ORP (mV)
IR88-MW31	11/30/2010	7.25	24.95	17.70	8.69	4.37	0.99	25.27	12.7	-278.2

ft - feet

btoc - below top of casing

SU - standard units

mS/cm - miliSiemens per centimeter

mg/L - milligram per liter

NTU - nephlometric turbidity units

mV - millivolts

TABLE 6-4 Groundwater Analytical Results Former UST-25 Phase I LSA Report MCB CamLej, North Carolina

NCCWOS		IR88-MW31	
	GCL	IR88-GW31-10D	
(January, 2010)		11/30/10	
1	5,000	120	
600	84,500	7.3	
500	85,500	14	
500	85,500	27	
600	260,000	44	
30	12,500	1.4 J	
700	NS	8.8	
300	990	0.16 J	
0.05	0.05	0.11 J	
6	6,000	7.2 J	
400	NS	50,000	
700	NC	1,200 J	
700	INO	75 U	
10,000	NS	75 U	
200	NC	2,500	
200	CVI	75 U	
	600 500 500 600 30 700 300 0.05 6	(January, 2010) * GCL	

NCGWQS - North Carolina Groundwater Quality Standard

GCL - Gross Contamination Levels

Bold box indicates exceedance of NC2L or the more conservative MCL

Bold text indicates exceedance of GCL

J - Analyte present, value may or may not be accurate or precise

U - The material was analyzed for, but not detected

μg/l - Micrograms per liter

 * - The MCL-Groundwater value is reported in place of the NCGWQS where the MCL value is more conservative.

NS - Not specified





PROJECT NUMBER: 180555.FI.MW

BORING NUMBER: 88-MW31

Sheet: 1 of 1

SOIL BORING LOG

PROJECT: RI 88/CTO-026	/MW Installation	LOCATION	: MCB Camp Lejeune, NC	
ELEVATION:	DRILLING CON	TRACTOR: Par	ratt Wolff	
DRILLING METHOD AND	EQUIPMENT: HSA CME-75			
WATER I EVELS.	STADT: 10/13/05	FINISH-	LOCCEP: D. Dov	

ATE	R LE	VELS:	-	START	r: 10/13/05 FINISH:LOGO	GER: D. Dry
>		SAMPI	-	STANDARD PENETRATION	SOIL DESCRIPTION	COMMENTS
DEPTH BELOW	S ERY		6"-6"-6" (N)	SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY OR CONSISTENCY, SOIL STRUCTURE, MINERALOGY	DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS TESTS AND INSTRUMENTATION	
0					Ground Surface	
- - -						PID/FID (ppm)
5-	5.0 7.0		2	5-7-6 (13)	Silt (ML), Uniform mixed material, dark green gray, damp, firm	VOC @ 1425 295/2,147 Air monitoring at background
- 10- - -	10.0 12.0		2	1-2-2 (4)	At 10 ft., Moist, soft with tan inclusions	VOC @ 1440 2,027/7,490
15- -	15.0 17.0		2	1-1-2 (3)	At 15 ft, Wet, soft	VOC @ 1450 1,409/3,460 Air monitoring at 0/0.5 ppm above background, VC detector
	18.0 20.0		2	2-1-3 (4)	Clay (CH), Dark brown, soft, plastic, moist	tube =0.0 ppm VOC @ 1510 55/272
25-					End of Boring at 20.0'	VOC soil samples collected at 5, 10 15 and 20 feet bgs, analysis by compuchem



PROJECT NUMBER	WELL NUMBER		
317567	88-MW31	SHEET 1	OF 1

WELL COMPLETION DIAGRAM





ocation:		AMP LEJEU			ect Number: Well ID:	1288	- HW3	<u> </u>	See.
vent:		-WE31 SITE	S	-	Sample ID:		8-GW		•
ate:	TOTAL PROPERTY OF THE PARTY OF	110	6		npling Team:	_ V. CL	ruaine p	an/Pr	DU
eather:	705 18	artly	doude	orver	4			451556	# 1307Le
otal Depth:		18	FT.(BTOC)			Me	asuring Device:	Hanna	# 09010
epth to wat		7.25	FT.(BTOC)				Date and Time:	See ta	ble below
ater Colum	Carrie	0.75	FT.			F 11 - 1		i	
ell Volume			GAL/FT.	- 415	-	Well Dia. (inches)	Volume (gallons/foot)		
otal Purge			GAL. A S	3(0)	,	0.75	0.023	1	
otal i argo	_	010	- Cir 121			1	0.041		
urge Devic	e:	blada	er ge	1000		2	0.163		
	2 	10-0	4	3		4	0.653	l	
						6	1.469		
					ELD PARAM				
Time	Depth to Water (ft bgs)	Temp. °C	Cond. mS/cm	DO mg/L	pH SU	ORP mV	Turbidity NTU	Flow Rate (mL/min)	Color / Odor / Comments
Stabiliza	tion Criteria	±10%	± 3%	± 10%	± 0.1	± 10 mV	± 10% or <10	(300-500)	Carried The Carried
330	7.95	25.21	3.893	0.59	9.94	-395.0	16.0	450	clear
335	9. (0)	25,09	3,910	0.32	9.77	-464.3	10.1	400	CIEDA
345	10.52	25.05	3.85		9.87	-400.9	4.86	350	
1350	11.12	25.15	3.936	0.19	9.48	-399.7	1.79	300	
1355	11,58	25:23	3.990	0.14	9.34	-394,2	2.34	11	
400	12.12	25.27	3,994	0.23	9.43	-3433	2.08	11	
405	12,55	25.29	3.963	0.18	9.59	-391.0	5.45	1.1	
410	13.10	25,31	3,977	0.21	9.50	-370.5	2.38) (
1415	13,52	25,33 25,25	4.181	1.43	8,96	-346.9	5.02		
1435	14.51	25.27	4.370	0.99	8 69		12.	- 15 - 11	
1422	17.65	-3161	7,110	0.11	3.6-1	(15.0		,,,,	
					SAMPLE DA	ATA			
ate: 🚶	30/10	Temp.	Cond.	DO	pН	ORP	Turbidity	Other:	Color / Odor / Comments
ime:	1515	°C	mS/cm	mg/L	SU	mV	NTU		
	ow-flow	25.27			8,69	-278,2	12.7		
ample infor	mation: method,		nber, size, and			1 0	SERVICE STREET		
_	Analy VOC				rvative CL	/3×	ontainer require 40 mL VOAs		No. of containers
	SVOCs (EP.	200		- ///	VA.	2×	1 Liter Amber		3 -2-6
	MADEP				CL	13×	40 mL VOAs		2
	MADEP	EPH		Н	CL	12+	1 Liter Amber	s	,2
	EPA 625 BNA	TEXT TO THE PROPERTY OF THE PARTY OF THE PAR			NA	1127	1 Liter Amber	(2	12
	· LEAD & CH	ROMIUM		H	NO3	17 x 2	50 mL or 500 mL	. Poly	
bservations	/Notos:				1.0				
otal Volume		5.5	gul pu	mb 24	asted	(3) (a) 13	126	FID: 0.0	Ppm 0=350 oder when op
IS/MSD:	YES	(NO)		MS ID:				3.2.	- · · · · · · · · · · · · · ·
				SD ID:					
Service and the service and th				ī.					
uplicate:	YES	NO)		Duplicate ID	!				.mf@ 1435 to
ignature(s):	Verd.	A	Ci						

Appendix C Soil and Groundwater Analytical Laboratory Reports and Chain-of-Custody Forms



CHAIN of CUSTODY

PLEASE BEAR DOWN AND PRINT LEGIBLY IN PEN

Page ____ of ___

-		X: (207) 775-4029				1			ALCOHOLD STATE			rage	7	
Clie	ent CZZM Hr	4		Gontai K B	EUA EUA	SHAV	V (Phone # (757)	671-	249	F (ax #		
Add	dress 3225710 (1	BELLE ST	City					State (/)			Zip Coc	le	7	
Pur	chase Order #	Pro	j. Name / N	o	10-U	1E3	14	87-13	0.75	Katahd	in Quote	#		
Bill	(if different than above)			Ad	dress	_						T.		
Sar	npler (Print / Sign) Con / N	HE A WAR	math.	bus	1/1	1 Och	low	Name and Post Office of the Owner, where the Owner, which is the Owner, where the Owner, which is the Owner, whis	ASSESSMENT OF THE OWNER, THE OWNE	THE RESERVE OF THE PERSON NAMED IN	STATE OF THE PARTY OF THE PARTY.	HA SHO	46/	
L	AB USE ONLY WORK ORD	ER #:	1				A	NALYSI I		ONTAE VATIVE		E		
RE	MARKS:	PROJECT NUMBER _			Filt. □Y,ĐN	Filt.	Filt. □Y¦©N	Filt.	Filt.	Filt.	Filt.	Filt.	Filt.	Filt. □Y □N
	PPING INFO: FED EX	☐ UPS	CLIEN	VT	西	BI/4+17	PREP PREP	Pace Prese						
	MP°C TEMP BLAI	NK I INTACT	□ NOT	INTACT	0	625	D C	12+1						
*	Sample Description	Date / Time coll'd	Matrix	No. of Cntrs.	MARK	72 62	3030C	DSS. 3050C						
	UST/817-GNO1-10D	12/1/1135	AQ	6	1	/	V	1						
	517817-GWD1-100-MS	12/1 /1135	16	6	/	V	/	/				,		
	UST1817-GNOT-180-50	12/1 /1135	ACR	4		1	V	V						
		/												
	Here in the second	/											,	
		/					4						- 1	
		/												
		/		490										
		/									d			
		/									1			
		/									11			
	<u> </u>	/												
		/												
		/									-			
		/												
		/												
	EDER AIRBIL	8726	15	48	50	37								
			eived By: (S				ned By: (9	Signature) Da	te / Ti	me R	eceived I	By: (Signa	ature)
1c	Hell 12	1/												
R	elinquished By: (Signature) D	ate / Time Rece	ived By: (S	ignature) F	Relinquish	ned By: (S	Signature) Da	te / Ti	me R	eceived I	By: (Signa	ature)



CHAIN of CUSTODY

PLEASE BEAR DOWN AND PRINT LEGIBLY IN PEN

	1 1
Page _/	of

Cli	ent			Conta		_		Phone #				ax#		
CH	2M HILL			REBE	EKHA	SHAL	/ (757)	671-	624	8 ()		
Ad	dress 5700 CLEVELAN	ID 57	City	VA E	SERCH	+	S	State /	-		Zip Cod	le		
Pu	rchase Order #	Proj	. Name / N	10. CTC	-WES	1/	4089	43.F	1.FS	Katahdi	n Quote	#		
Bill	(if different than above)			Ac	Idress									
Sa	mpler (Print / Sign) VERD AN	UP CUNNING	IAM/	Verd	1	a Ce	-1	-		es To:	THE RESERVE TO SHARE THE PARTY OF THE PARTY	2. 54.	9W	
L	AB USE ONLY WORK ORDE						A		RESER	VATIVE:				
RE	MARKS:	ROJECT NUMBER _			Filt.	FILL	Filt.	Filt.	Filt.	Filt.	Filt.	Filt.	Filt.	Filt.
SH	IPPING INFO: FED EX	☐ UPS	☐ CLIEN	NT	7	1410		30						
	RBILL NO:	V TINITAGE	TNOT	INITA OT	27	SBVA	TOPAL PLACE	7650C						
TE	MP°C TEMP BLAN		□ NOT		M	8	33							
*	Sample Description	Date / Time coll'd	Matrix	No. of Cntrs.	NAD	100	10 PM	DSS.						
	TR78-GW09-ID-100D	11/30 /1730	AQ	6	V	V	V	V						
-	AST45-578T@	/								1				
	IR84-GW17-10D	12/1 /1445	AQ	6	V		V							
		/												
		/												
		/						Y-i						
		/												
	XIV	/												
		/												
	The state of the s	/												
		/												
		/												
		/												
		/												
		/												
		/												
CON	MENTS Fed & #	: 2336	36	11-	+	8	126	154	8 5	53	7			
R	elinguished By: (Signature) Da	te / Time Rece	ived By: (S	ignature) A	lelinquish	ned By: (S	Signature) Da	te / Tir	ne R	eceived E	3y: (Signa	ature)
R	elinquished By: (Signature)		ived By: (S	ignature) R	lelinquist	ned By: (\$	Signature) Da	te 1/ Tir	me A	eceived E	3y: (Signa	ature)



CHAIN of CUSTODY

PLEASE BEAR DOWN AND PRINT LEGIBLY IN PEN

Page / of /


Client CH2M HILL	: (207) 775-4029	Contr	act REKAL	a SHA	U (Phone # 757	671-	6248	Fr.	ax#		
Address 5700 CLORIAND	ST			4					Zip Cod	e		
Purchase Order #		Name / No.	NK2	1/1	1069	43 F	1.75	Katahdii	n Quote	#		
Bill (if different than above)			ddress	0	10							
Sampler (Print / Sign) VERD AN	NA CUNNIN	131+#K1/1	Dir	Lu	Kelk	400	Copi	es To:	SHI	tw		
LAB USE ONLY WORK ORDE	ER #:			E II			PRESER	VATIVES	i i			
REMARKS:	ROJECT NUMBER		□\ Ør	Filt. DY ØN	□Y ØN	MY ON	□Y □N	OY ON	□Y □N	DY ON	OY ON	□Y □N
SHIPPING INFO: FED EX	□ UPS	☐ CLIENT	T	101 - AWA	6 4 4	100						
TEMP°C TEMP BLAN	IK INTACT	☐ NOT INTAC	T Q	(25 B)	176+ 30304	2 6						
Sample Description	Date / Time coll'd	Matrix No. of Control	MAC	34 (2)	四四日	DISS.						
UST 1817-GWO1-18D-SD	2/1/135	10 2	/	124	1	1						
1888-GW31-10D	1111 1111	AQ 4	V	1	Pg (N						
IR78-GW09-1-10D	11/30 /1725	10 006	1	V	V	V						
	/											
	/											
	/											
	/											
	/											
	/											
	/											
	/											
	/											
	1											
	/											
	/											
COMMENTS				-								
Fed ex #								1,5				
	ate / Time Received	ved By: (Signatu	re)	Relinquisl	ned By: (Signature) Da	te / Tir	ne A	Received	By: (Sign	ature)
		ved By: (Signatu	re)	Relinquisl	ned By: (Signature	Da	te / Tir	me F	Received	By: (Sign	ature)



CHAIN of CUSTODY

PLEASE BEAR DOWN AND PRINT LEGIBLY IN PEN

Client CH2M HILL	(207) 775-4029	Q.	Contact	BA S	SUALI	F (Phone #	(-71-	674		ax #		
Address 5700 CLEVELAN	D ST	City /A			<u> Tienv</u>		tate VA		9210	Zip Cod	e		
Purchase Order #		, Name / No.			21 /		-		Katahdi	n Quote	#		
Bill (if different than above)				Iress	4	120							
Sampler (Print / Sign) FRD AN	NA CUNNIN	ISHAM						Copi	es To: 7	2. St	HAW		
LAB USE ONLY WORK ORDE	IR #:			-	File			PRESER	VATIVES	5		E14	
REMARKS:	ROJECT NUMBER _			JY JN	DY DIN	DY DN	DY DN	DY BIN	DY DN	DY QN	DY ON	Filt.	DY DN
SHIPPING INFO: Ø FED EX	☐ UPS	☐ CLIENT			1707	G.	350		18	SNE			
AIRBILL NO:	D 0P5	D CLIENT		to	EWA	ちゃろ	8	/PH	38	71/2/1			
TEMP'C TEMP BLAN	K INTACT	☐ NOT IN	TACT	CT TTT	625	76 th	13030XI	4	200B	602			
* Sample Description	Date / Time coll'd	Matrix N	No. of Ontrs.	MADE	EPP 6	TOTAL ESPE	PSS. F	MADEP	9 503	17 P			
WE31-FB113010-100	11/30 /1635	AQ	310	/	V	/		V	1				
	12/1 /1545	AQ P	311	1	1	V	/	1	/				
JR64-GW17-10D	12/1 /1445	AQ S	5					V	1				
IR78-GW09-10-100	1130/130	AQ S	5					V	V				
UST 1817-GWOI-18P-MS	12/1/1135	AQ	5					V	1				
UST-1817-GWO1-140-SD	12/1/1135	AQ.	5	-				V	V				
(PUBLES UST 1817-GND)-160	12/1 /1135	AG .	5					V	V				
IR88-GW31-100	11/30 /15/5	AQ.	5					1		V			
IR78-GW189-1-10D	11/30 /1725	AG	5					/	/				
	/												
	/							9.					
	/			j.									
	/		-										
	/	200	2										
		#											
FEDER PIRE!	8726 /	548	3 .	5.5.	37								
Relinquished By: (Signature) Da	ite / Time Rece	elved By: (Sig				ned By: (\$	Signature) Da	ite / Tir	me F	Received	By: (Sign	ature)
Relinquished By: (Signature)	te / Time Rece	eived By: (Sig	ınature)	F	telinquish	ned By: (S	Signature) Da	ite / Tir	me F	Received	By: (Sign	ature)





Report of Analytical Results

Client: CH2MHill Lab ID: SD7472-10

Client ID: IR88-GW31-10D

Project: MCB Camp Lejeune CTO-WI

SDG: WE31-1

Sample Date: 30-NOV-10 Received Date: 02-DEC-10 Extract Date: 09-DEC-10

Extracted By: TTC

Extraction Method: SW846 8260B

Lab Prep Batch: WG86093

Analysis Date: 09-DEC-10

Analyst: TTC

Analysis Method: SW846 8260B

Matrix: AQ % Solids: NA

Report Date: 04-JAN-11

Compound	Qualifier	Result	Units	Dilution	LOQ	ADJ LOQ	ADJ MDL	ADJ LOD
Toluene		44.	ug/L	1	1	1.0	0.27	0.50
Benzene		120	ug/L	1	1	1.0	0.26	0.50
Ethylbenzene		7.3	ug/L	1	1	1.0	0.21	0.50
m+p-Xylenes		14.	ug/L	1	2	2.0	0.59	1.0
o-Xylene		27.	ug/L	1	1	1.0	0.25	0.50
Dibromofluoromethane		89.8	%					
Toluene-d8	W 196	95.0	%			59		
p-Bromofluorobenzene		104.	%			15, 31		
1,2-Dichloroethane-d4		91.5	%					





Report of Analytical Results

Client: CH2MHill Lab ID: SD7472-10

Client ID: IR88-GW31-10D

Project: MCB Camp Lejeune CTO-WI

SDG: WE31-1

Sample Date: 30-NOV-10 Received Date: 02-DEC-10 Extract Date: 03-DEC-10

Extracted By:CB

Extraction Method: EPA 625 Lab Prep Batch: WG85796 Analysis Date: 04-DEC-10

Analyst: WAS

Analysis Method: EPA 625

Matrix: AQ % Solids: NA

Report Date: 14-DEC-10

Compound	Qualifier	Result	Units	Dilution	LOQ	ADJ LOQ	ADJ MDL	ADJ LOD
Bis(2-Chloroethyl) Ether	U	4.1	ug/L	1	5	5.1	1.0	4.1
1,3-Dichlorobenzene	U	4.1	ug/L	1	5	5.1	1.7	4.1
1,4-Dichlorobenzene	U	4.1	ug/L	1	5	5.1	2.0	4.1
1,2-Dichlorobenzene	J	3.4	ug/L	1	5	5.1	1.8	4.1
N-Nitroso-Di-N-Propylamine	U	4.1	ug/L	1	5	5.1	0.78	4.1
Hexachloroethane	U	4.1	ug/L	1	5	5.1	1.7	4.1
Nitrobenzene	U	4.1	ug/L	1	5	5.1	1.0	4.1
Isophorone	U	4.1	ug/L	1	5	5.1	0.85	4.1
Bis(2-Chloroethoxy) Methane	U	4.1	ug/L	1	5	5.1	0.90	4.1
1,2,4-Trichlorobenzene	U	4.1	ug/L	I	5	5.1	1.8	4.1
Hexachlorobutadiene	U	4.1	ug/L	1	5	5.1	1.6	4.1
Dimethyl Phthalate	U	4.1	ug/L	1	5	5.1	0.92	4.1
2,6-Dinitrotoluene	U	4.1	ug/L	1	5	5.1	0.62	4.1
2,4-Dinitrotoluene	U	4.1	ug/L	1	5	5.1	0.47	4.1
Diethylphthalate	U	4.1	ug/L	1	5	5.1	0.76	4.1
4-Chlorophenyl-Phenylether	U	4.1	ug/L	1	5	5.1	1.1	4.1
4-Bromophenyl-Phenylether	U	4.1	ug/L	1	5	5.1	1.1	4.1
Hexachlorobenzene	U	4.1	ug/L	1	5	5.1	0.93	4.1
Di-N-Butylphthalate		8.8	ug/L	1	5	5.1	0.78	4.1
Butylbenzylphthalate	U	4.1	ug/L	1	5	5.1	0.55	4.1
3,3'-Dichlorobenzidine	U	4.1	ug/L	1	5	5.1	1.8	4.1
Bis(2-Ethylhexyl) Phthalate	JB	2.1	ug/L	1	5	5.1	0.57	4.1
Di-N-Octylphthalate	U	4.1	ug/L	1	5	5.1	0.68	4.1
2-Fluorophenol		39.0	%					
Phenol-d6		21.1	%					
Nitrobenzene-d5		82.1	%					
2-Fluorobiphenyl		79.8	%					
2,4,6-Tribromophenol		104.	%					
Terphenyl-d14		84.9	%					





Report of Analytical Results

Client: CH2MHill Lab ID: SD7472-10RA Client ID: IR88-GW31-10D

Project: MCB Camp Lejeune CTO-WI

SDG: WE31-1

Sample Date: 30-NOV-10 Received Date: 02-DEC-10 Extract Date: 03-DEC-10

Extracted By: CB Extraction Method: SW846 3510

Lab Prep Batch: WG85798

Analysis Date: 17-DEC-10

Analyst: JCG

Analysis Method: SW846 M8270C

Matrix: AQ % Solids: NA

Report Date: 23-DEC-10

Compound	Qualifier	Result	Units	Dilution	LOQ	ADJ LOQ	ADJ MDL	ADJ LOD
Naphthalene	В	7.2	ug/L	1	.2	0.20	0.065	0.10
2-Methylnaphthalene		1.4	ug/L	1	.2	0.20	0.078	0.10
Acenaphthylene	U	0.10	ug/L	1	.2	0.20	0.055	0.10
Acenaphthene		0.38	ug/L	1	.2	0.20	0.065	0.10
Fluorene	J	0.16	ug/L	1	.2	0.20	0.062	0.10
Phenanthrene	U	0.10	ug/L	1	.2	0.20	0.052	0.10
Anthracene	U	0.10	ug/L	1	.2	0.20	0.045	0.10
Fluoranthene	U	0.10	ug/L	1	.22	0.22	0.074	0.10
Pyrene	U	0.10	ug/L	1	.2	0.20	0.060	0.10
Benzo (a) anthracene	U	0.10	ug/L	1	.2	0.20	0.047	0.10
Chrysene	U	0.10	ug/L	1	.2	0.20	0.037	0.10
Benzo (b) Fluoranthene	U	0.10	ug/L	1	.27	0.28	0.091	0.10
Benzo(k)fluoranthene	U	0.10	ug/L	1	.2	0.20	0.050	0.10
Benzo(a)pyrene	U	0.10	ug/L	1	.2	0.20	0.067	0.10
Indeno (1,2,3-cd) pyrene	J	0.11	ug/L	1	.2	0.20	0.053	0.10
Dibenzo (a,h) anthracene	U	0.10	ug/L	1	.21	0.21	0.071	0.10
Benzo(g,h,i)perylene	U	0.10	ug/L	1	.2	0.20	0.066	0.10
2-Chloronaphthalene	U	0.10	ug/L	1	.2	0.20	0.073	0.10
2-Methylnaphthalene-D10	*	41.4	%					
Fluorene-D10	*	24.3	%					
pyrene-d10		93.7	%					





Extractable Petroleum Hydrocarbon (EPH) Analysis

Client: CH2MHill SDG: WE31-1 Client Sample ID: IR88-GW31-10D Date Collected: 30-NOV-10 KAS Sample ID: SD7472-10RE Date Received: 02-DEC-10 Analytical Method: MA DEP EPH 04-1.1 Date Extracted: 13-DEC-10 Prep Method: SW846 3520 Date Reported: 05-JAN-11 Ma

atrix:	AQ	Percent Solids:	NA
atrix:	AQ	Percent Solids:	NA

EPH Range Results	Results	PQL	LOD	MDL	Units	DF	Date Analyzed	Qual
Unadjusted C11-C22 Aromatics	62	100	75	50	ug/L	1	18-DEC-10	JВ
C9-C18 Aliphatics	75	100	75	50	ug/L	1	18-DEC-10	U
C19-C36 Aliphatics	75	100	75	50	ug/L	1	18-DEC-10	U
C11-C22 Aromatics	62	100	75	50	ug/L	1	18-DEC-10	JB

Recovery	Acceptance Range	Date Analyzed Qual
49	40-140	18-DEC-10
49	40-140	18-DEC-10
52	40-140	18-DEC-10
79	40-140	18-DEC-10
53	40-140	18-DEC-10
	49 49 52 79	49 49 40-140 52 40-140 79 40-140

^{*} Fractionation Surrogates.

¹ Hydrocarbon Range data exclude concentrations of any surrogate(s) and/or internal standards eluting in that range.

² C11-C22 Aromatic Hydrocarbons exclude the concentration of Target PAH Analytes.

³ Diesel PAH Analytes.





Volatile Petroleum Hydrocarbon (VPH) Analysis

Client: CH2MHill

SDG: WE31-1

Client Sample ID: IR88-GW31-10D

Date Collected: 30-NOV-10

KAS Sample ID: SD7472-10

Date Received: 02-DEC-10

Analytical Method: MA DEP VPH 04-1.1

Date Extracted: 06-DEC-10

Date Reported: 04-JAN-11

Prep Method: SW846 5030B Matrix: AQ

Percent Solids: NA

The second secon								
VPH Range Results	Results	PQL	LOD	MDL	Units	DF	Date Analyzed	Qual
Unadjusted C5-C8 Aliphatics	11000	100	75	50	ug/L	1	06-DEC-10	E
Unadjusted C9-C12 Aliphatics	3000	100	75	50	ug/L	1	06-DEC-10	E
C5-C8 Aliphatics	11000	100	75	50	ug/L	1	06-DEC-10	E
C9-C12 Aliphatics	320	100	75	50	ug/L	1	06-DEC-10	E
C9-C10 Aromatics	2700	100	75	50	ug/L	1	06-DEC-10	E

VPH Surrogate Recoveries	Recovery	Acceptance Range	Date Analyzed	Qual
2,5-Dibromotoluene (FID)	. 109	70-130	06-DEC-10	
2,5-Dibromotoluene (PID)	99	70-130	06-DEC-10	

¹ Hydrocarbon Range data exclude concentrations of any surrogate(s) and/or internal standards eluting in that range.

² C5-C8 Aliphatic Hydrocarbons exclude the concentration of Target Analytes eluting in that range.

³ C9-C12 Aliphatic Hydrocarbons exclue the concentration of Target Analytes cluting in that range AND concentration of C9-C10 Aromatic Hydrocarbons.





Volatile Petroleum Hydrocarbon (VPH) Analysis

Client: CH2MHill

Client Sample ID: IR88-GW31-10D KAS Sample ID: SD7472-10DL2

Analytical Method: MA DEP VPH 04-1.1 Prep Method: SW846 5030B

Matrix: AQ

SDG: WE31-1

Date Collected: 30-NOV-10

Date Received: 02-DEC-10

Date Extracted: 07-DEC-10

Date Reported: 06-JAN-11

Percent Solids: NA

VPH Range Results	Results	PQL	LOD	MDL	Units	DF	Date Analyzed	Qua		
Unadjusted C5-C8 Aliphatics	42000	2000	1500	1000	ug/L	20	07-DEC-10	E		
Unadjusted C9-C12 Aliphatics	3600	2000	1500	1000	ug/L	20	07-DEC-10			
C5-C8 Aliphatics	42000	2000	1500	1000	ug/L	20	07-DEC-10	E		
C9-C12 Aliphatics	1200	2000	1500	1000	ug/L	20	07-DEC-10	J		
C9-C10 Aromatics	2500	2000	1500	1000	ug/L	20	07-DEC-10			

	VPH Surrogate Recoveries	Recovery	Acceptance Range	Date Analyzed	Qual
Γ	2,5-Dibromotoluene (FID)	86	70-130	07-DEC-10	
	2,5-Dibromotoluene (PID)	90	70-130	07-DEC-10	

¹ Hydrocarbon Range data exclude concentrations of any surrogate(s) and/or internal standards eluting in that range. 2 C5-C8 Aliphatic Hydrocarbons exclude the concentration of Target Analytes eluting in that range.

³ C9-C12 Aliphatic Hydrocarbons exclue the concentration of Target Analytes eluting in that range AND concentration of C9-C10 Aromatic Hydrocarbons.





Volatile Petroleum Hydrocarbon (VPH) Analysis

Client: CH2MHill

SDG: WE31-1 Date Collected: 30-NOV-10

Client Sample ID: IR88-GW31-10D

Date Received: 02-DEC-10

KAS Sample ID: SD7472-10DL3

Analytical Method: MA DEP VPH 04-1.1

Prep Method: SW846 5030B

Date Extracted: 08-DEC-10

Date Reported: 06-JAN-11

Matrix: AQ

Percent Solids: NA

VPH Range Results	Results	PQL	LOD	MDL	Units	DF	Date Analyzed	Qual
Unadjusted C5-C8 Aliphatics	50000	10000	7500	5000	ug/L	100	08-DEC-10	
Unadjusted C9-C12 Aliphatics	7500	10000	7500	5000	ug/L	100	08-DEC-10	U
C5-C8 Aliphatics	50000	10000	7500	5000	ug/L	100	08-DEC-10	
C9-C12 Aliphatics	7500	10000	7500	5000	ug/L	100	08-DEC-10	U
C9-C10 Aromatics	7500	10000	7500	5000	ug/L	100	08-DEC-10	U

VPH Surrogate Recoveries	Recovery		Acceptance Range	Date Analyzed	Qual
2,5-Dibromotoluene (FID)	93	1	70-130	08-DEC-10	
2,5-Dibromotoluene (PID)	88		70-130	08-DEC-10	

¹ Hydrocarbon Range data exclude concentrations of any surrogate(s) and/or internal standards eluting in that range.

2 C5-C8 Aliphatic Hydrocarbons exclude the concentration of Target Analytes eluting in that range.

³ C9-C12 Aliphatic Hydrocarbons exclue the concentration of Target Analytes eluting in that range AND concentration of C9-C10 Aromatic Hyrdrocarbons.



CHAIN of CUSTODY

PLEASE BEAR DOWN AND PRINT LEGIBLY IN PEN

Page ____ of _

Client CH2M HJLL	Rehe	Sec. 11	shau		Phone # 757)	671-	-6279	Fax # ()		
Address Stoc Kleveland St. Suite (C) City								Code 53	462	
Purchase Order # 942685 Proj. Name / I							Katahdin C	Puote #		
Bill (if different than above)	Add	iress		4						
Sampler (Print / Sign) Daviel Brown	D	en	2	-			es To:			
LAB USE ONLY WORK ORDER #: KATAHDIN PROJECT NUMBER	July 1	Filt.	Filt.	Α Filt.		S AND C PRESERV Filt.	electric results in the facility	ETYPE Filt. Filt.	Filt.	Filt.
REMARKS:		DY DN	OY ON	DY DN	DY ON	DY DN	OY ON O	YONOYON	DYDN	JY ÖN
SHIPPING INFO:	ENT					Lead				
	INTACT	7	Ho	61	20	101				
* Sample Description Date / Time coll'd Matrix	No. of Cntrs.	Ve	17	1	20	leto	100			
AST 45-5781-5861 4-5-60 18930 Scil	8	X	X	X	X	1				
15745 5781-58d-4-5+00-15 10930 Seil	8	X	X	X	X	X	*	The second		
15145 5781-5801-4-5-103-50 10930 Scil	8	X	X	X	X	X				
AST 45-5781-5861-7-9-10 14/14/19/1030 5011	8	X	X	X	X	x	35			
SOIL TRIPBLAME /1	6	X	X							1
WE31-EB121410 12/4/10/1400 6W	10	X.	X	X	X	X	1			
/ /										
							THE STATE OF			
										16
		3								
						1			12.0	
, ,										
COMMENTS /							1			
Relinquished By: (Signature)	(Signature	e)	Relinquis	hed By:	(Signatur	e) D	ate / Time	Received	By: (Sign	nature)
Relinquished By: (Signature) Date / Time Received By:	(Signature	e)	Relinquis	hed By:	(Signatur	re) D	ate / Time	e Received	i By: (Sign	nature)



CHAIN of CUSTODY

PLEASE BEAR DOWN AND

-	Fax:	(207) 775-4029	ing the Carolina		1. 特别于1.		Fituit	II LEGI	DET III	LLIV	10000	Page .	of			
Clie	Client CHZM HILL Repo					etha shalu (757)671-6279 ()										
Address 5700 (leveland St. City Virginia Beach																
Pui	Purchase Order # Camp Le Jeune WE31 Proj. Name / No. 408943, FI, FS Katahdin Quote #															
Bill	Bill (if different than above) 942085 Address															
Sa	mpler (Print / Sign) Day iel															
LAB USE ONLY WORK ORDER #:				ANALYSIS AND CONTAINER TYPE PRESERVATIVES												
REMARKS:					Filt. □Y □N	Filt.	Filt.	Filt.	Filt.	Filt. □Y □N	Filt. □Y □N	Filt.	Filt.			
SHIPPING INFO:			608				27/10									
AIRBILL NO:			8				Total Chronium									
TEMP°C TEMP BLANK INTACT			☐ NOT	INTACT	5	I	=	20	3							
*	Sample Description	Date / Time coll'd	Matrix	No. of Cntrs.	200	Up	EPH	51/6	Toto	The BAN						
	UST 1817-5801-5-7-100	12/13/19/1120	5011	8	X	X	X	X	X							
	UST1817-5801-10-12-101)	/1140		8					X							
	UST 1817-5BO1-15-17-10D	/1200	1	8					X	7				green .		
	UST 1601-5801-4-5-100	/1350		8					X							
	UST 1601-58010-4-5-10D	/1355		8					X							
	UST 1601-5801-7-9-100	/1410		8					X							
	UST25-5801-4-5-101)	1/1600		8	1	1	1	V				2 57				
	SOIL TRIP BLANK	/		6	X	X										
		/														
	and the second second	/														
		/	La Argent													
		/	in the same													
		/														
		/									1 100					
	and the second	/					4 1									
		/														
COMMENTS																
Relinquished By: (Signature) Date / Time Received By: (Signature) Relinquished By: (Signature) Date / Time Received By: (Signature)																
Om Par 12/14/16 1600																
Relinquished By: (Signature) Date / Time Received By: (Signature) Relinquished By: (Signature) Date / Time Received By: (Signature) Relinquished By: (Signature) Date / Time Received By: (Signature) Relinquished By: (Signature) Date / Time Received By: (Signature) Relinquished By: (Signature) Date / Time Received By: (Signature) Date /											ature)					



CHAIN of CUSTODY

PLEASE BEAR DOWN AND PRINT LEGIBLY IN PEN

Page of

	The state of the s	(201) 113-4029									rage .	01	
				petha Shaw () ()									
Add	iress 5700 cleveland	d St. Suite,	City Uil	gini	or Bed	och s	state	VA	Z	Zip Code	e 23	1462	?
Pur	Purchase Order # 942085 Proj. Name / No. 408943, FI, F5 Katahdin Quote #												
Bill	(if different than above)		A	ddress	To your								
Sar	Sampler (Print/Sign) Daniel Brown Deci					Name and Address of the Owner, where			es To:				
LA	AB USE ONLY WORK ORDE			A			ONTAINE VATIVES	ER TYP	E				
KATAHDIN PROJECT NUMBER				Filt.	Filt.	Filt.	Filt.	Filt.	Filt.	Filt. JY □N	Filt.	Filt.	Filt. □Y □N
SH	SHIPPING INFO:							1/1					
AIRBILL NO:				5	1		U	Chronius					
TE	MP°C TEMP BLAN	K INTACT	☐ NOT INTAC	2	Hd	PF	SVO	0					
*	Sample Description	Date / Time coll'd	Matrix No. of Cntrs.		14	2	5.6	Cotol					
	WE31-EB121310	12/13/14/1800	w 10	X	X	X	X	X					
	WE31- FB121310	2/13/10/1740	W 10	X	X	X	X	X					
		1						1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					
		/						7-09	CONTRACTOR				
		/											
	*	/					23-3-			(even			
		/				2 15							
		/											
		/				100 60							
		/			427								
		1											
		/					0 00000		1 - 12				
		/								2			
		/											
	Talk the same arms	/											
-	The State of the S	/						E / 276					
COMMENTS													
Relinquished By: (Signature) Date / Time Received By: (Signature) Relinquished By: (Signature) Date / Time Received By: (Signature)								nature)					
Relinquished By: (Signature) Date / Time Received By: (Signature) Relinquished By:							(Signatur	re) D	ate / Tir	me -	Received	By: (Sig	nature)